

Length // ► Feed direction

Width

Perforated sheet


Open Area: 16 %

C20 T50 90°



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²
Steel						
	1.00	500856	156655			6.6
	1.50	501720	156776	156777	156778	9.9
	2.00	502479	156880	156881	156882	13.2
	2.99	502548	156895	156896	156897	19.7
Pre-galvanised						
DX51D	St 02 Z	1.00	500758	156647	156648	6.6
		1.50	501621	156760	156761	9.9
		2.00	502392	156864	156865	13.2
		3.00	502787	156917		19.8
Aluminium						
EN AW-1050A H24	Al 99,5% hh	1.50	500962	156669	156670	3.4
		2.00	501818	156793	156794	4.5
		3.00	502607	156910	156911	6.8
// PVC coated on one side		1.50	501056	156680	156681	3.4
		2.00	501911	156805	156806	4.5
EN AW-5005 H24 EQ // PVC coated on both sides	AlMg 1 hh EQ	2.00	501974	156505	156554	4.5
EN AW-5005 H24 EQ // pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502814	156819	156820	4.5
		3.00		158269		6.8
Stainless steel						
X5CrNi18-10 2B	1.4301 IIIC	1.00	500520	156619	156620	6.6
		1.50	501357	156700	156701	9.9
		2.00	502210	156834	156835	13.2
X5CrNi18-10 2B // polished 1 side grain 240, PVC 1 side		1.00	500595	156627		6.6
		1.50	501469	156738	156739	9.9
		2.00	502276	156845	156846	13.2
X5CrNi18-10 2B // polished 2 sides grain 240, PVC 2 sides		1.50	501414	156715	156716	9.9
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	500666	156637	156638	6.6
		1.50	501527	156746		9.9
		2.00	502323	156851		13.2

C20 T50 90°



Square holes
staggered pitch (CT)
w = 20 mm
p = 50 mm
c = 30 mm
Open area: 16 %