

Length // ► Feed direction

Width

Perforated sheet


Open Area: 52.89 %

C8 U11



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.00	500850	154580	155061	155062	3.7	
	1.50	501714	101047	155063	155064	5.5	
	2.00	502473	155065	155066	155067	7.4	
Pre-galvanised							
DX51D	St 02 Z	1.00	500752	155068	155069	155070	3.7
		1.50	501615	155071	155072	155073	5.5
		2.00	502386	155074	155075	155076	7.4
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.00	500278	155101	155102	155103	1.3
		1.50	500956	155104	155105	155106	1.9
		2.00	501812	155107	155108	155109	2.5
EN AW-5754 H22	AlMg 3 hh	1.00	500363	155113	155114	155115	1.3
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.00	500514	155077	155078	155079	3.7
		1.50	501352	155083	155084	155085	5.5
		2.00	502205	155081			7.4
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00	500439	155090			3.7
		1.50	501267	155091		155093	5.5
		2.00	502147	155094			7.4
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	500660	155095	155096		3.7
		1.50	501522	155097	155098	155099	5.5
		2.00	502318	155100			7.4

C8 U11



Square holes
square pitch (CU)
w = 8 mm
p = 11 mm
c = 3 mm
Open area: 52.89 %

* Not all materials are available in all formats and sheet thicknesses.