

# Perforated sheet


Open Area: 25 %

## C8 U16



| Material (desired formats also available in powder-coated finish) | Material thickness | Desired format | Small format 1000 x 2000 mm | Medium format 1250 x 2500 mm | Large format 1500 x 3000 mm | Weight kg/m <sup>2</sup> |
|---|--------------------|----------------|-----------------------------|------------------------------|-----------------------------|--------------------------|
| <b>Steel</b>  |                    |                |                             |                              |                             |                          |
|   | 1.00               | 503277         | 158587                      | 158591                       | 158595                      | 5.9                      |
|   | 1.50               | 503278         | 158588                      | 158592                       | 158596                      | 8.8                      |
|   | 2.00               | 503279         | 158589                      | 158593                       | 158597                      | 11.8                     |
|   | 2.99               | 503280         | 158590                      | 158594                       | 158598                      | 17.6                     |
| <b>Pre-galvanised</b>   |                    |                |                             |                              |                             |                          |
| DX51D   | St 02 Z            | 1.00           | 503281                      | 158599                       | 158603                      | 5.9                      |
|   |                    | 1.50           | 503282                      | 158600                       | 158604                      | 8.8                      |
|   |                    | 2.00           | 503283                      | 158601                       | 158605                      | 11.8                     |
|   |                    | 3.00           | 503284                      | 158602                       | 158606                      | 17.7                     |
| <b>Aluminium</b>  |                    |                |                             |                              |                             |                          |
| EN AW-1050A H24   | Al 99,5% hh        | 1.00           | 503285                      | 158611                       | 158615                      | 2.0                      |
|   |                    | 1.50           | 503286                      | 158612                       | 158616                      | 3.0                      |
|   |                    | 2.00           | 503287                      | 158613                       | 158617                      | 4.1                      |
|   |                    | 3.00           | 503288                      | 158614                       | 158618                      | 6.1                      |
| // PVC coated on one side   |                    | 1.00           | 503289                      | 158623                       | 158626                      | 2.0                      |
|   |                    | 1.50           | 503290                      | 158624                       | 158627                      | 3.0                      |
|   |                    | 2.00           | 503291                      | 158625                       | 158628                      | 4.1                      |
| EN AW-5005 H24 EQ// PVC coated on one side                        | AlMg 1 hh EQ       | 1.00           | 503292                      | 158632                       | 158636                      | 2.0                      |
|   |                    | 1.50           | 503293                      | 158633                       | 158637                      | 3.0                      |
|   |                    | 2.00           | 503294                      | 158634                       | 158638                      | 4.1                      |
|   |                    | 3.00           | 503295                      | 158635                       | 158639                      | 6.1                      |
| EN AW-5005 H24 EQ // PVC coated on both sides                     | AlMg 1 hh EQ       | 2.00           | 503296                      | 158644                       | 158645                      | 4.1                      |
| EN AW-5005 H24 EQ // pre-anodised 2 sides E6/C0, PVC 1 side       |                    | 1.50           | 503297                      | 158647                       | 158648                      | 3.0                      |
|   |                    | 2.00           | 503298                      | 158650                       | 158651                      | 4.1                      |
| <b>Stainless steel</b>  |                    |                |                             |                              |                             |                          |
| X5CrNi18-10 2B  | 1.4301 IIIC        | 1.00           | 503299                      | 158653                       | 158654                      | 5.9                      |
|   |                    | 1.50           | 503300                      | 158656                       | 158657                      | 8.8                      |
|   |                    | 2.00           | 503301                      | 158659                       | 158660                      | 11.8                     |
|   |                    | 3.00           | 158662                      |                              |                             | 17.7                     |
| // PVC coated on one side   |                    | 1.00           | 503302                      | 158663                       | 158664                      | 5.9                      |
|   |                    | 1.50           | 503303                      | 158666                       | 158667                      | 8.8                      |
|   |                    | 2.00           | 503304                      | 158669                       | 158670                      | 11.8                     |
| X2CrNiMo17-12-2 2B  | 1.4404 IIIC        | 1.00           | 503305                      | 158672                       | 158673                      | 5.9                      |
|   |                    | 1.50           | 503306                      | 158675                       | 158676                      | 8.8                      |
|   |                    | 2.00           | 503307                      | 158678                       | 158679                      | 11.8                     |
| X6CrNiMoTi17-12 2B  | 1.4571 IIIC        | 1.00           | 503308                      | 158681                       | 158685                      | 5.9                      |
|   |                    | 1.50           | 503309                      | 158682                       | 158686                      | 8.8                      |
|   |                    | 2.00           | 503310                      | 158683                       | 158687                      | 11.8                     |
|   |                    | 3.00           | 503311                      | 158684                       | 158688                      | 17.7                     |

C8 U16



Square holes square pitch (CU)  
 w = 8 mm  
 p = 16 mm  
 c = 8 mm  
 Open area: 25 %

\* Not all materials are available in all formats and sheet thicknesses.