

Length // ► Feed direction

Width

Perforated sheet


Open Area: 27.78 %

LC5x20 U12x30



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.50	501673	157641	153421	153605	8.5	
Pre-galvanised							
DX51D	St 02 Z	1.50	501573	156961	156962	156963	8.5
	2.00	502351	156964	156965	156966	11.3	
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.50	500913	150138	150330	150516	2.9
		2.00	501772	150139	150331	150517	3.9
// PVC coated on one side		1.50	501015	150637	150750		2.9
		2.00	501869	150638	150751		3.9
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501100	150935			2.9
EN AW-5005 H24 EQ							
// pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502004	151359	151418	151477	3.9
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.00	500479	152241	152386		5.7
		1.50	501317	152242	152387	152515	8.5
X5CrNi18-10 2B // polished							
1 side grain 240, PVC 1 side		1.00	500567	152679			5.7
		1.50	501434	157642	152775	152865	8.5
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.50	501232	151974		152094	8.5

LC5x20 U12x30



Slotted holes square pitch
 $w = 5 \text{ mm}$. $l = 20 \text{ mm}$
 $c_1 = 7 \text{ mm}$. $c_2 = 10 \text{ mm}$
 $p_1 = 12 \text{ mm}$. $p_2 = 30 \text{ mm}$
 Open area: 27.78 %