

Length // ► Feed direction

Width

Perforated sheet


Open Area: 41.97 %

LR10x50 Z19x60



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²
Steel						
	1.00	500818	153233		158574	4.6
	1.50	501681	157941	153413	153596	6.8
	2.00	502444	153234	153414	153597	9.1
Pre-galvanised						
DX51D	St 02 Z	1.00	500720	153764		4.6
		1.50	501582	157009	157010	6.8
		2.00	502358	157012	157013	9.1
Aluminium						
EN AW-1050A H24	Al 99,5% hh	1.50	500922	150127	150319	2.4
		2.00	501781	150128	150320	3.1
		3.00	502584	150129	150321	4.7
// PVC coated on one side		1.50	501024	150632	150740	2.4
		2.00	M 501878	157942	150741	3.1
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501109	150922		2.4
		3.00	502646		151246	4.7
EN AW-5005 H24 EQ // PVC coated on both sides	AlMg 1 hh EQ	2.00	501952	156503	156552	3.1
EN AW-5005 H24 EQ // pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502013	151354	151413	3.1
EN AW-5754 H22	AlMg 3 hh	1.00	502817		151841	1.6
Stainless steel						
X5CrNi18-10 2B	1.4301 IIIC	1.00	500486	152226	152372	4.6
		1.50	501324	152227	152373	6.8
		2.00	502181	152228	152374	9.1
X5CrNi18-10 2B // polished 1 side grain 240, PVC 1 side		1.00	500572	156414		4.6
		1.50	501441	152672	152767	6.8
		2.00	502253	152673	152768	9.1
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.50	501239	151965		6.8
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	500634	153006	153095	4.6

LR10x50 Z19x60



Slotted holes
staggered pitch
w = 10 mm. l = 50 mm
c₁ = 9 mm. c₂ = 10 mm
p₁ = 19 mm. p₂ = 60 mm
Open area: 41.97 %