

Perforated sheet


Open Area: 32.62 %

LR2x20 Z5x24



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.00	500819	153225			5.3	
	1.50	501682	153226	153401	153584	7.9	
	2.00	502445	100048	153402	153585	10.6	
Pre-galvanised							
DX51D	St 02 Z	1.00	500721	153758		5.3	
		1.50	501583	157015	157016	7.9	
		2.00	502359	157018	157019	10.6	
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.50	500923	150118	150308	150495	2.7
		2.00	501782	150119	150309	150496	3.6
// PVC coated on one side		1.50	501025	150622	150730		2.7
		2.00	501879	150623	150731		3.6
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501110	150910			2.7
EN AW-5005 H24 EQ							
// pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502014	151349	151408	151467	3.6
EN AW-5754 H22	AlMg 3 hh	1.00	500334	151615	151749	151838	1.8
		1.50	501170	151616	151750		2.7
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.00	500487	152215	152361		5.3
		1.50	501325	101646	152362	152499	7.9
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00	500417	151955			5.3
		1.50	501240	151956		152083	7.9
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	500635	152999	153091		5.3
		1.50	501504	153000			7.9

LR2x20 Z5x24



Slotted holes
staggered pitch
w = 2 mm. l = 20 mm
c₁ = 3 mm. c₂ = 4 mm
p₁ = 5 mm. p₂ = 24 mm
Open area: 32.62 %

* Not all materials are available in all formats and sheet thicknesses.