

Perforated sheet


Open Area: 34.56 %

LR3x20 Z7x24



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.50	M 501684	157627	153405	153588	7.7	
	2.00	502447	153230	153406	153589	10.3	
Pre-galvanised							
DX51D	St 02 Z	1.50	501585	157028	157029	157030	7.7
		2.00	502361	157031	157032	157033	10.3
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.50	500925	150121	150312	150499	2.7
		2.00	501784	150122	150313	150500	3.5
// PVC coated on one side		1.50	501027	150626	150734		2.7
		2.00	501881	150627	150735		3.5
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501111	150915			2.7
EN AW-5005 H24 EQ // pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502016	151351	151410	151469	3.5
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.50	501327	152220	152365	152501	7.7
X5CrNi18-10 2B // polished		1.50	501443	152667	152762	152854	7.7
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.50	501242	151959		152085	7.7

LR3x20 Z7x24



Slotted holes
staggered pitch
w = 3 mm. l = 20 mm
c₁ = 4 mm. c₂ = 4 mm
p₁ = 7 mm. p₂ = 24 mm
Open area: 34.56 %