

Length // ► Feed direction

Width

## Perforated sheet


Open Area: 39.88 %

# LR4x20 Z8x24



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m <sup>2</sup>
<b>Steel</b>						
	1.00	500821	153231			4.7
	1.50	M 501685	101519	153407	153590	7.1
	2.00	502448	153232	153408	153591	9.4
<b>Pre-galvanised</b>						
DX51D	St 02 Z	1.00	500723	153760		4.7
		1.50	501586	157034	157035	7.1
		2.00	502362	157037	157038	9.4
<b>Aluminium</b>						
EN AW-1050A H24	Al 99,5% hh	1.50	500926	150123	150314	2.4
		2.00	501785	150124	150315	3.2
// PVC coated on one side		1.50	501028	150628	150736	2.4
		2.00	501882	150629	150737	3.2
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501112	150917		2.4
EN AW-5005 H24 EQ // pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502017	151352	151411	3.2
EN AW-5754 H22	AlMg 3 hh	1.00	500336	151619	151753	1.6
<b>Stainless steel</b>						
X5CrNi18-10 2B	1.4301 IIIC	1.00	500489	152221	152366	4.7
		1.50	501328	152222	152367	7.1
		2.00	502182	152223	152368	9.4
X5CrNi18-10 2B // polished 1 side grain 240, PVC 1 side		1.00	500574	152668		4.7
		1.50	501444	152669	152763	7.1
		2.00	502254	152670		9.4
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00	500419	151960		4.7
		1.50	501243	151961	152086	7.1
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	500637	153002	153093	4.7

LR4x20 Z8x24



Slotted holes  
staggered pitch  
w = 4 mm. l = 20 mm  
c<sub>1</sub> = 4 mm. c<sub>2</sub> = 4 mm  
p<sub>1</sub> = 8 mm. p<sub>2</sub> = 24 mm  
Open area: 39.88 %