

Length // ► Feed direction

Width

Perforated sheet


Open Area: 43.81 %

LR5x20 Z9x24



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.00	500822	100050	153409		4.4	
	1.50	501686	100051	153410	153593	6.6	
	2.00	502449	100052	153411	153594	8.8	
Pre-galvanised							
DX51D	St 02 Z	1.00	500724	153761	153874	4.4	
		1.50	501587	153762	153875	6.6	
		2.00	502363	153763	153876	8.8	
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.00	500258			1.5	
		1.50	500927	150126	150317	2.3	
		2.00	M 501786	100473	150318	3.0	
		3.00			158347	4.6	
// PVC coated on one side		1.50	501029	150630	150738	2.3	
		2.00	501883	150631	150739	3.0	
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501113	150919		2.3	
EN AW-5005 H24 EQ							
// pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502018	151353	151412	151471	3.0
EN AW-5754 H22	AlMg 3 hh	1.00	500337	151621	151754	1.5	
		1.50	501171	151622	151755	2.3	
		2.00	502077	151623	151756	3.0	
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.00	500490	152224	152369	158402	4.4
		1.50	501329	100474	152370	152504	6.6
		2.00	502183	152225	152371	152505	8.8
// PVC coated on one side		1.00		158373			4.4
X5CrNi18-10 2B // polished							
1 side grain 240, PVC 1 side		1.50	501445	152671	152765	152857	6.6
		2.00	502255	156413			8.8
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00	500420	151962			4.4
		1.50	501244	151963		152087	6.6
		2.00	502129	151964			8.8
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	500638	153004	153094		4.4
		1.50	501505	153005			6.6
		2.00		158461			8.8

LR5x20 Z9x24



Slotted holes
staggered pitch
w = 5 mm. l = 20 mm
c₁ = 4 mm. c₂ = 4 mm
p₁ = 9 mm. p₂ = 24 mm
Open area: 43.81 %