

Length // ► Feed direction

Width

Perforated sheet


Open Area: 17.25 %

Rhomb aligned



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.50	501721	153256	153431	153615	9.7	
	2.00	502480	153257	153432	153616	13.0	
Pre-galvanised							
DX51D	St 02 Z	1.50	501622	157074	157075	9.7	
		2.00	502393	157077	157078	13.0	
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.50	500963	150150	150342	3.4	
		2.00	501819	150151	150343	4.5	
// PVC coated on one side		1.50	501057	150644	150761	3.4	
		2.00	501912	157647	150762	4.5	
EN AW-5005 H24 EQ// PVC coated on one side	AlMg 1 hh EQ	1.50	501139	150947		3.4	
		3.00	502669		151272	6.7	
EN AW-5005 H24 EQ // pre-anodised 2 sides E6/C0, PVC 1 side		2.00	502045	151364	151423	151482	4.5
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.50	501358	152251	152395	152522	9.7
X5CrNi18-10 2B // polished 1 side grain 240, PVC 1 side		1.50	501470	152685	152782	152871	9.7
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.50	501271	151981		152099	9.7
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.50	501528	156449		9.7	

ROMB 60



Creativ Line
Open area: 17.25 %