

Length // ► Feed direction

Width

Perforated sheet


Open Area: 58.05 %

R16 T20



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²	
Steel							
	1.00	500880	153173			3.3	
	1.50	501746	153174	153340	153520	4.9	
Pre-galvanised							
DX51D	St 02 Z	1.00	500782	153697		3.3	
Aluminium							
EN AW-1050A H24	Al 99,5% hh	1.50	500988	150058	150246	150432	1.7
		2.00	501844	150059	150247	150433	2.3
// PVC coated on one side		1.50	501080	150599	150705		1.7
		2.00	501935	150600	150706		2.3
EN AW-5005 H24 EQ							
// pre-anodised 2 sides E6/C0,							
PVC 1 side		2.00	502065	151332	151391	151450	2.3
EN AW-5754 H22	AlMg 3 hh	1.00	500386	151555	151703	151807	1.1
Stainless steel							
X5CrNi18-10 2B	1.4301 IIIC	1.00	500544		152147		3.3
		1.50	501383	152148	152311	152449	4.9
		2.00		158408			6.6
X5CrNi18-10 2B // polished							
1 side grain 240, PVC 1 side		1.00	500615	152727			3.3
		1.50	501493	152616	152728	152819	4.9
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00	500458	151908			3.3
		1.50	501293	151909		152066	4.9

R16 T20



Round holes 60 degree staggered pitch (RT)
 w = 16 mm
 p = 20 mm
 Open area: 58.05 %

Not all materials are available in all formats and sheet thicknesses.