

Length // ► Feed direction

Width

Perforated sheet


Open Area: 29.62 %

R2 T3.5



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²
Steel						
	0.50		101682			2.8
	0.75		100386			4.1
	1.00		100088	100310	153468	5.5
	1.50		100089	100264	158584	8.3
	2.00		100090	101582		11.1
Pre-galvanised						
DX51D	St 02 Z	0.70	101617	101765		3.9
		1.00	100233	153781	153877	5.5
		1.50	101656	153782	153878	8.3
		2.00	101657	153783		11.1
Aluminium						
EN AW-1050A H24	Al 99,5% hh	0.80	158354			1.5
		1.00 ^M	100185	150189	158327	1.9
		1.50	100186	150190	158329	2.9
		2.00	150008	150191	150377	3.8
EN AW-5754 H22	AlMg 3 hh	1.00	151497	151651		1.9
		1.50	151498	151652		2.9
		2.00	151499	151653		3.8
Stainless steel						
X5CrNi18-10 2B	1.4301 IIIC	0.80	158398			4.4
		1.00	100012	100516		5.5
		1.50	100013	100506		8.3
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00	158417	158419		5.5
		1.50	158425			8.3
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00	156628	153021		5.5
		1.50	100039	153022		8.3
X6Cr17 2R	1.4016	1.00	158223			5.5
X6CrNiTi 18-10 2B	1.4541	1.50	158482			8.3
Brass						
CuZn37		0.80	158217			4.8
		1.00	158507			6.0
		1.50	158508			9.0

R2 T3.5



Round holes 60 degree
staggered pitch (RT)
w = 2 mm
p = 3.5 mm
Open area: 29.62 %