

Length // ► Feed direction

Width

Perforated sheet


Open Area: 40.31 %

R4 T6



| Material (desired formats also available in powder-coated finish) | Material thickness | Desired format | Small format 1000 x 2000 mm | Medium format 1250 x 2500 mm | Large format 1500 x 3000 mm | Weight kg/m ² |
|---|--------------------|----------------|--------------------------------|---------------------------------|--------------------------------|-----------------------------|
| Steel | | | | | | |
| | 0.75 | | 158555 | | | 3.5 |
| | 1.00 | 500890 | 100101 | 101396 | 153477 | 4.7 |
| | 1.50 | 501753 | 100102 | 100350 | 100790 | 7.0 |
| | 2.00 | 502511 | 100103 | 100352 | 100507 | 9.4 |
| | 2.99 | 502570 | 100104 | 101571 | 100508 | 14.0 |
| Pre-galvanised | | | | | | |
| DX51D | St 02 Z | 0.70 | 500242 | 158491 | 100512 | 3.3 |
| | | 0.75 | | | 158498 | 3.5 |
| | | 1.00 | 500792 | 100238 | 100256 | 4.7 |
| | | 1.50 | 501651 | 101587 | 101591 | 7.0 |
| | | 2.00 | 502423 | 101588 | 153793 | 9.4 |
| | | 3.00 | 502807 | 153665 | 159578 | 14.1 |
| Aluminium | | | | | | |
| EN AW-1050A H24 | Al 99,5% hh | 0.80 | 500252 | 101432 | 101447 | 1.3 |
| | | 1.00 | 500309 | 100191 | 150199 | 1.6 |
| | | 1.50 | 500994 | 100192 | 150200 | 2.4 |
| | | 2.00 | 501850 | 100193 | 101395 | 3.2 |
| | | 3.00 | 502631 | 150570 | 150676 | 4.8 |
| EN AW-5005 H24 EQ | | | | | | |
| // pre-anodised 2 sides E6/C0, | | | | | | |
| PVC 1 side | | 2.00 | | 158262 | | 3.2 |
| EN AW-5754 H22 | AlMg 3 hh | 1.00 | 500396 | 157925 | 100327 | 1.6 |
| | | 1.50 | 501217 | 151506 | 100522 | 2.4 |
| | | 2.00 | 502119 | 151507 | 151662 | 3.2 |
| Stainless steel | | | | | | |
| X5CrNi18-10 2B | 1.4301 IIIC | 0.80 | | 158474 | | 3.7 |
| | | 1.00 | 500550 | 100017 | 100322 | 4.7 |
| | | 1.50 | 501389 | 100018 | 152271 | 7.0 |
| | | 2.00 | 502237 | 100356 | 152272 | 9.4 |
| X5CrNi18-10 2B // polished | | | | | | |
| 2 sides grain 240, PVC 2 sides | | 1.50 | | 101702 | | 7.0 |
| X2CrNiMo17-12-2 2B | 1.4404 IIIC | 1.00 | 500463 | 151864 | | 4.7 |
| | | 1.50 | 501298 | 151865 | | 7.0 |
| X6CrNiMoTi17-12 2B | 1.4571 IIIC | 1.00 | 500694 | 152891 | 153026 | 4.7 |
| | | 1.50 | 501554 | 152892 | 153027 | 7.0 |
| | | 2.00 | | 101618 | | 9.4 |
| X6CrNiTi 18-10 2B | 1.4541 | 1.50 | | 158483 | 158484 | 7.0 |

R4 T6



Round holes 60 degree
staggered pitch (RT)
w = 4 mm
p = 6 mm
Open area: 40.31 %