

Length // ► Feed direction

Width

Perforated sheet


Open Area: 51.02 %

R6 T8



Material (desired formats also available in powder-coated finish)	Material thickness	Desired format	Small format 1000 x 2000 mm	Medium format 1250 x 2500 mm	Large format 1500 x 3000 mm	Weight kg/m ²
Steel						
	0.50		101683			1.9
	1.00	500895	153154	153308	153485	3.8
	1.50	503259	158233	158234	158235	5.8
	2.99		101715			11.5
Pre-galvanised						
DX51D	St 02 Z	1.00 ^M 500797	100244	153800	153894	3.8
		1.50 503258	158230	158231	158232	5.8
Aluminium						
EN AW-1050A H24	Al 99,5% hh	1.00 500314	150024	150210	150393	1.3
		1.50 503256	158224	158225	158226	2.0
		2.00 158227	158227	158228	158229	2.6
EN AW-5754 H22	AlMg 3 hh	1.00 500401	151516	151670		1.3
Stainless steel						
X5CrNi18-10 2B	1.4301 IIIC	1.00 500555	100275	152280	152421	3.8
		1.50	101793			5.8
		2.00	101814			7.7
X2CrNiMo17-12-2 2B	1.4404 IIIC	1.00 500468	151874			3.8
X6CrNiMoTi17-12 2B	1.4571 IIIC	1.00 500699	152901	153033		3.8

R6 T8



Round holes 60 degree staggered pitch (RT)
 w = 6 mm
 p = 8 mm
 Open area: 51.02 %